



RECOMMEND PCB LAYOUT(TOLERANCE= ± 0.05)

N: NUMBER OF CONTACTS

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	ZQJ 11/18/2014	~	ZQJ 11/18/2014
B	ADD P/N CODE	CJJ 11/18/2014	~	

NOTES:

- MATERIAL
 - INSULATOR:THERMOPLASTIC(U194 V-0).
 - CONTACT MATERIAL: COPPER ALLOY.
- SPECIFICATION
 - CURRENT RATING: 1.5 Amp.
 - INSULATION RESISTANCE: 1000M Ω Min.
 - DIELECTRIC WITHSTANDING: 600VAC.
 - CONTACT RESISTANCE: 50m Ω Max.
 - OPERATING TEMPERATURE: -40°C TO +105°C.

GENERAL TOLERANCE	ANGLE	TOLERANCE
X	$\pm 5^\circ$	
X	± 0.38	
.XX	± 0.25	

DRAWING TYPE	CUSTOMER	SHEET	1 OF 1
SCALE	1:1		
DRAWING NO.			

PROJECTION	TITLE
UNITS	1.0MM PIN HEADER
SHEET SIZE	BOARD SPACES RIGHT ANGLE
A4	SERIES LL1013-04E

慈溪蓝翎电子有限公司
CIXI LANLING ELECTRONICS CO., LTD.